



**NCS6722A N4**

**NETAŞ CLOUD  
SERVER**

**DATASHEET**

NCS6722A N4, is a new-generation 2U2 socket general rack server, which supports 2 AMD®EPYC® scalable processors family.

NCS6722 N4 uses a high-density, modular, and streamline design.

It features high capability, large capacity, high reliability, easy expansion, and easy management, which is widely applicable to interconnection, network, cloud computing, big data, and virtualization.

### **1. High Density, High Performance**

- Supports two AMD®EPYC® Scalable Processors family.
- Provides 32 DDR5 memory slots, with a maximum rate of 4,800MT/s
- Provides high-speed I/O performance and supports high-performance NVMe SSD.

### **2. High Scalability, High Bandwidth**

- Provides up to 25x 2.5" slots or up to 12x 3.5" slots and + 4x 2.5" (rear) slots to meet the requirements for large-capacity storage.
- Supports NVMe SSDs optionally to provide high-speed I/O interfaces and solves the bottleneck of slow hard disk access in traditional solutions.
- Provides multiple storage combinations and RAID card configuration options to flexibly configure local storage in accordance with service requirements.
- Provides the powerful expansion capability and supports up to 12 PCIe 5.0 expansion slots.

### 3. High Availability, High Reliability

- The good heat dissipation design improves system reliability, and effectively extends the life of components and reduces costs.
- The hard disks, power supplies, and fans support hot swapping, improving the availability of the system.
- Supports RAID 0, 1, 5, 6, 10, 50, 60 supports power-off protection, and provides multiple data protection solutions for users.
- Power modules support 1+1 redundancy, and fans support N+1 redundancy, improving system reliability.
- Supports TPM/TCM.

### 4. Convenient Management, Easy Maintenance

- Provides the intelligent management platform, implementing out-of-band monitoring of resources such as CPUs, memories, hard disks, fans, power supplies, and networks.
- Supports standard interfaces such as IPMI, SNMP, and Redfish, so that the platform can be integrated with third-party management systems.
- Supports automatic deployment, firmware upgrade, and remote operations to improve deployment and O&M efficiency.
- Provides powerful the KVM function.

### 5. Green, Energy Saving, Environment Protection

- 80PLUS high-efficiency platinum/titanium power supplies are used to support power capping.
- Supports high-voltage DC and low-voltage DC technologies to improve energy utilization.
- Intelligent rotation speed adjustment and silence design  
Lead-free design and environmental protection



## 6. Teknik Özellikler

Technical Specification	NCS6722A N4 2U Rack Server
<b>Feature</b>	
<b>From</b>	2U Rack Server
<b>CPU</b>	1/2 AMD®EPYC® scalable processor
<b>Memory</b>	Support up to 24 DDR5 memory slots with maximum rate of 4,800 MT/s
<b>Raid controller</b>	Supports RAID 0/1/5/6/10/50/60 and power-off protection
<b>Local Storage</b>	Provides a maximum of 25x 2.5" slots, or maximum of 12x 3.5" slots, + 4x 2.5" slots,
<b>I/O Module</b>	
<b>Network Resources</b>	Supports 2x OCP3.0 interfaces,
<b>PCIe slots</b>	Supports up to 12 PCIe slots: 2x OCP dedicated slots, 8x PCIe standard slots
<b>External Equipment interface</b>	4x USB interface 2x rear USB3.0 1x front USB3.0 1x front USB2.0  2x VGA interface (1x front, 1x rear) 1x RS232 - Serial port
<b>Hardware Management Interface</b>	Support 1 independent GE management network interface
<b>Display</b>	Integrated display cards, Supporting the optional configuration of PCIe standard display cards
<b>OS</b>	
<b>Compatible OS</b>	Compatible with mainstream server operating systems: Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Enterprise Linux, Vmware ESXI, Ubuntu,

Physical Features	
<b>Power</b>	Supports 1+1 hot/swappable redundant power supplies. (Optional) 550 W/800 W/1200 W/1600 W/2000 W/2700 W/3200 W high-efficiency platinum/titanium power supply Supports 110V/220V AC, 240V/336V high-voltage DC and -48V DC
<b>Fan</b>	Four groups of high-efficiency fans, N+1 redundancy and intelligent heat dissipation system
<b>Environmental conditions</b>	Operating temperature: +5 °C to +45 °C (depending on the configuration, refer to the technical documentation for details) Storage temperature: -40 °C to +65 °C Operating humidity: %8 – %90 RH, no condensation Transportation and storage humidity: %5 – %95 RH, no condensation Altitude: ≤ 3.000m. When the altitude is 900m. higher, the operating temperature is reduced by 1°C for every 300m. higher. If the altitude is more than 3.000m., you cannot configure mechanical hard disks.
<b>Size</b>	432 mm x 87,6 mm x 780 mm (W x H x D), excluding flanges and guide rails Standard 19-inch rack (>=1m deep)
<b>Weight with full configuration</b>	The equipment with the maximum configuration is about 40Kg. (Excluding guide rails)
<b>Certificate</b>	CE, CCC